

GMMP 規格

規格 \ PUMP TYPE	GMMP / GMML / GMMH	
	60Hz	50Hz
最大扬程 (TDH Max.)(M)	30	21
最大流量 (Capacity Max.)(L/min)	90	80
最高温 (Temperature Max.)	150℃ / 280℃ / 150℃	
最低温 (Temperature Min.)	-30℃ / -30℃ / -80℃	
最大比重 (Specific Gravity Max.)	2	
最大黏度 (Viscosity Max.)	120 cp	
设计压力 (Design pressure)	6 kgf/cm ²	
口径(入/出) Bore (Suc/Dis)	15/15 ^A ~ 25/20 ^A	
Flange Rating	PT THREAD	
叶轮样式 (Impeller Type)	Closed	
马达型式 (Motor Type)	Horiaontal 2P 90W / 180W / 360W / 550W	
材质 (Casing)	SCS14 (SUS316)	
垫片 (Gasket)	PTFE / GRAPHITE / GRAPHITE	
轴承 (Bearing)	SSiC	
轴套 (Sleeve)	SSiC (Shaft)	
磁铁 (Magnet)	R.earth Nd / R.earth Nd / SmCo	
泵样式 (Models fo Pump)	4	
轴承样式 (Type of Bearing)	1	