

GMMP 規格

規格 \ PUMP TYPE	GMMP / GMML / GMMH	
	60Hz	50Hz
最大揚程 (TDH Max.)(M)	30	21
最大流量 (Capacity Max.)(L/min)	90	80
最高溫 (Temperature Max.)	150℃ / 280℃ / 150℃	
最低溫 (Temperature Min.)	-30℃ / -30℃ / -80℃	
最大比重 (Specific Gravity Max.)	2	
最大黏度 (Viscosity Max.)	120 cp	
設計壓力 (Design pressure)	6 kgf/cm ²	
口徑(入/出) Bore (Suc/Dis)	15/15 ^A ~ 25/20 ^A	
Flange Rating	PT THREAD	
葉輪樣式 (Impeller Type)	Closed	
馬達型式 (Motor Type)	Horiaontal 2P 90W / 180W / 360W / 550W	
材質 (Casing)	SCS14 (SUS316)	
墊片 (Gasket)	PTFE / GRAPHITE / GRAPHITE	
軸承 (Bearing)	SSiC	
軸套 (Sleeve)	SSiC (Shaft)	
磁鐵 (Magnet)	R.earth Nd / R.earth Nd / SmCo	
泵樣式 (Models fo Pump)	4	
軸承樣式 (Type of Bearing)	1	