

GMP 規格

PUMP TYPE		GMP / GML / GMH	
规格			
		60Hz	50Hz
最大扬程 (TDH Max.)(M)		60	40
最大流量 (Capacity Max.)(L/min)		550	450
最高温 (Temperature Max.)		150℃ / 150℃ / 280℃	
最低温 (Temperature Min.)		-30℃ / -80℃ / -30℃	
最大比重 (Specific Gravity Max.)		2	
最大黏度 (Viscosity Max.)		330 cp	
设计压力 (Design pressure)		10 kgf/cm ²	
口径(入/出) Bore (Suc/Dis)		25/20 ^A – 50/40 ^A	
Flange Rating		JIS 10K / ANSI150	
叶轮样式 (Impeller Type)		Closed	
马达型式 (Motor Type)		Horiaontal 2P , 4P 0.75kW – 5.5kW	
材质 (Casing)		SCS14 (SUS316)	
垫片 (Gasket)		PTFE / GRAPHITE / GRAPHITE	
轴承 (Bearing)		SSiC	
轴套 (Sleeve)		SSiC	
磁铁 (Magnet)		R.earth Nd / R.earth Nd / SmCo	
泵样式 (Models fo Pump)		7	
轴承样式 (Type of Bearing)		1	